

Specifications	4KCHANGER-TC2
Transmitter	
HDMI Bandwidth	600MHz / 18.0Gbps
HDMI Resolution	480P,720P,1080P/24,30,50,60Hz, 4Kx2K/24,30,60Hz.
Mini DisplayPort Resolution	800x600, 1024x768, 10280x1024,1600x900, 1600x1200,
	1920x1080, 1920x1200, 2560x1440, 3840x2160, 4096x2160
VGA Resolution	1024x768, 1280x1024, 1600x900, 1600x1200, 1920x1080
USB 3.1 C Resolution	1024x768, 10280x1024,1600x900, 1600x1200, 1920x1080
	1920x1200, 2560x1440, 3840x2160, 4096x2160
HDMI Output Resolution	480P,720P,1080P/24,30,50,60Hz, 4Kx2K/24,30,60Hz.
	VGA video in only supports 1920x1080p as output resolution
Audio Format	Dolby True HD, DTS HD, Dolby, Atoms, Dolby Digital 5.1,
	Dolby Digital Plus, DTS 5.1, LPCM
HDCP	2.2
Input Port	Mini DisplayPort X 1
	HDMI X 1
	VGA X 1
	Audio X 1 -3.5mm Stereo Jack
	USB 3.1 C X 1
	Ethernet X 1 - RJ45 at Cat.5e/6 (Pass Thru)
Output Port	RJ45X1
	USB 2.0 A X 1 -5V/ 1.5 Amp BC 1.2
	USB 3.1 C X 1- 5V/ 2.0 Amp
	Ethernet X 1 - RJ45 at Cat.5e/6 (Pass Thru)
Control Port	Select button X 1 -
Power Supply	24VDC / 1.5 Amp (US,UK,EU Power Plug)
Power Consumption	36 W - Max.
Chassis Material	Metal
Panel Color	Silver
Operating Temperature	0°C -40°C / 32°F -104°F
Storage Temperature	-15°C -55°C / 5°F -131°F
Humidity	5 - 85% RH (Non-Condensing)
Dimension LXWXH	7.2 in (184 mm) X 3.1 in (80 mm) X 3.6 in (90 mm)
Weight	1,270 g
Transmitter	
HDMI Bandwidth	225MHz / 6.75Gbps
HDMI Output Resolution	480P,720P, 1080P/24,30,50,60Hz, 4Kx2K/50,60Hz.
	VGA video in only supports 1920x1080p as output resolution
Audio Format	2 Channel 16/20/34bit , PCM at 32/44.1/48KHz
	IEC 61937 32/44.1/48KHz, up to 8 Channel
	Dolby Ture HD, DTS HD, Dolby, Atoms, Dolby Digital 5.1,
	Dolby Digital Plus, DTS 5.1, LPCM
HDCP	2.2
Input Port	RJ45 X 1
Output Port	HDMI X 1
Power Supply	POC
Chassis Material	Metal
Chassis Color	Black
Operating Temperature	0°C -40°C / 32°F -104°F
Storage Temperature	-15°C -55°C / 5°F -131°F
Humidity	5 - 85% RH (Non-Condensing)
Dimension LXWXH	4.3 in (110 mm) X 2.17 in (55 mm) X 0.94 in (24 mm)
Weight	125 g

Unit Number	Description
4KCHANGER-TC1	4KCHANGER Table Connective with input of Type C, VGA+3.5mm Audio, Mini DP & HDMI, auto-detect sources, switch botton, single HDMI output
4KCHANGER-TC2	4KCHANGER Table Connective with a Extender for distance extention and connection via 30M RJ45 Cat. 6 ; input : Type C, VGA+3.5mm Audio, Mini DP & HDMI, auto-detect sources, switch button, single HDMI output